



### GENERAL NOTES:

TURNLOCK-100HGEC = 1 DIRECTION ELECTRICALLY CONTROLLED.  
TURNLOCK-100HGEC2 = 2 DIRECTION ELECTRICALLY CONTROLLED.

GALVANIZED STEEL CONSTRUCTION.

MINIMUM PAD SIZE SHOWN. MUST BE LEVEL WITHIN 1/4".

ALLOW 1" [25.4mm] FOR REMOVAL OF 2PC COVER

### ELECTRICAL NOTES:

POWER SERVICE OPTIONS:

1. 24 VDC
2. 110 VAC SINGLE PHASE
3. 220 VAC SINGLE PHASE 50/60HZ
4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

4 LOCATIONS AVAILABLE FOR CONDUIT ACCESS.

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

### CODED NOTES:

1. BARRIER ASSEMBLY, WELDED - GALVANIZED STEEL
2. SHIELD ASSEMBLY, WELDED (2) - GALVANIZED STEEL
3. ROTOR ASSEMBLY, WELDED (3) - GALVANIZED STEEL
4. CEILING PLATE - GALVANIZED STEEL
5. MECHANISM CHANNEL - STEEL (S.C.), POWDERCOATED
6. 2 PC CHANNEL COVER - STAINLESS STEEL
7. BASE PLATE - ANODIZED ALUMINUM
8. BOTTOM BEARING
9. BOTTOM FLANGE
10. ANCHOR BOLTS (9), PROVIDED

