



GENERAL NOTES:

TRILOCK-75CA-RN: ONE DIRECTION ELECTRICALLY CONTROLLED
TRILOCK-75CA-RN2: TWO DIRECTIONS ELECTRICALLY CONTROLLED

OPTIONAL PLATFORM AND RAILING AVAILABLE.
OPTIONAL POWDERCOATING AVAILABLE.

20.5" & 22" PASSAGE WIDTH AVAILABLE - 38" CABINET REQUIRED

ELECTRICAL NOTES:

- POWER SERVICE OPTIONS:
1. 24 VDC
 2. 110 VAC SINGLE PHASE
 3. 220 VAC SINGLE PHASE 50/60HZ
 4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. COVER - STAINLESS STEEL
2. CABINET - STAINLESS STEEL
3. REVEAL - STAINLESS STEEL
4. ARM - STAINLESS STEEL Ø 1-1/4" 16GA (3) TYP
5. ACCESS DOORS (2) TYP
6. HUB - POWDERCOATED ALUMINUM

PASSAGE WIDTH & ARM LENGTH		
PASSAGE WIDTH	ARM LENGTH	TRUE ARM LENGTH
19.5"	17"	17.59

