



SECTION A-A
BOTTOM BEARING/BASE PLATE
SCALE 1:2

GENERAL NOTES:

TURNLOCK-150ASTG2 = 2 DIRECTIONS ELECTRICALLY CONTROLLED.

CLEAR ANODIZED ALUMINUM CONSTRUCTION.

MINIMUM PAD SIZE SHOWN. MUST BE LEVEL WITHIN 1/4".

ALLOW 2" [50.8MM] FOR REMOVAL OF 2 PC COVER.

ELECTRICAL NOTES:

POWER SERVICE:
110 VAC SINGLE PHASE

15A MAINS SERVICE REQ'D

4 LOCATIONS AVAILABLE FOR CONDUIT ACCESS.

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. BARRIER ASSEMBLY, WELDED - ANODIZED ALUMINUM W/ LEXAN PANELS
2. SHIELD ASSEMBLY, WELDED - ANODIZED ALUMINUM W/ LEXAN PANELS
3. ROTOR ASSEMBLY, WELDED (3) - ANODIZED ALUMINUM
4. CEILING PLATE - ANODIZED ALUMINUM
5. MECHANISM CHANNEL - POWDERCOATED STEEL W/ SPEED CONTROL
6. 2 PC CHANNEL COVER WIDE - STAINLESS STEEL
7. BASE PLATE - ANODIZED ALUMINUM
8. BOTTOM BEARING
9. BOTTOM FLANGE
10. ELECTRIC KEY - ENTRY/EXIT
11. CARD READER BOX
12. LIGHTS (ENTRY/EXIT)
13. HEEL PROTECTORS
14. ANCHOR BOLTS (11), PROVIDED

OPTIONS:

- FIELD CONFIGURABLE CCW FAIL LOCK ENTRY / FAIL SAFE EXIT
- ELECTRIC KEY OVERRIDE ENTRY / EXIT
- STANDARD SPEED CONTROL
- SOLENOID ACTIVATION SWITCH FC ENTRY/EXIT
- STANDARD MECHANICAL LOCK

